


PRODUKT-INFO

UM-5/MJ HIGH PRECISION SMD CRYSTAL

FEATURES

1. UM-5/MJ is UM-5 lead-bent gull wing type with metal jacket for easy surface mounting.
2. Wide frequency range.
3. Tight tolerance and stability over temperature.
4. Miniature and compact.

Actual Size




APPLICATION

Ideal for telecommunications such as pagers (beepers), hand-held radios.

ELECTRICAL SPECIFICATIONS	
Model	UM-5
Frequency Range	10.0 MHz ~ 200.0 MHz
Crystal Cut	AT-cut
Load Capacitance (C_L)	8 pF ~ 32 pF, Series (Customer Spec.)
Drive Level	100 μ W (500 μ W max.)
Frequency Tolerance (at +25°C)	± 3 ppm / ± 5 ppm / ± 10 ppm / ± 20 ppm / ± 30 ppm
Equivalent Series Resistance	30 Ω ~ 150 Ω max.
Frequency Stability	± 5 ppm / ± 10 ppm / ± 15 ppm / ± 20 ppm / ± 25 ppm / ± 30 ppm / ± 50 ppm / ± 100 ppm
Operating Temperature Range	-10°C to +60°C, -20°C to +70°C, -40°C to +85°C option
Storage Temperature Range	-50°C to +105°C
Aging (at +25°C) first year	± 3 ppm / year max.

Dimensions (Units: mm)

Package: UM-5/MJ



7.9 x 3.5 x 8.2/12.5

*Crystals...
and more*

Now available



**digital electronic
siegfried lehrer gmbh**
Rudolf-Wanzl-Str. 3+5
D-89340 Leipzig / Germany
www.digitallehrer.de
digital@digitallehrer.de

Telefon +49 (0) 82 21 / 7 08 - 0 · Telefax +49 (0) 82 21 / 7 08 - 80

All specifications subject to change without notice.